

# 761GX-M754

REV:B--->1.0


REV:1.0

PCB: 15-K97-011000


BOM: 89-200-K97100

P1.COVER SHEET  
P2.BLOCK  
03.ClawHammer\_1\_HyperTransport  
04.ClawHammer\_2\_DDR  
05.ClawHammer\_3\_Misc  
06.ClawHammer\_4\_Power  
07.DDR DIMM  
08.Termination Resistors  
09.761GX-1 LDT, PCI Express  
10.761GX-2 MUTIOL & Others  
11.761GX-3 Power and Ground  
12.761GX-4 Power, Decoupling  
13.PCI Express\_X16  
14.VGA Connector  
15.Clock Generator  
16.964-1 PCI/IDE/HyperZip  
17.964-2 LPC/MII/CPU/GPIO  
18.964-3 USB/SATA  
19.964-4 Power  
20.PCI 1  
21.PCI 2 & PCI3  
22.IDE  
23.Super I/O (ITE8712)  
24.HM/FAN  
25.COM1/COM2/LPT  
26.KB/MS/ROM/FDC  
27.ATX/Panel/RTC  
28.USB  
29.RT8800 (CPU VCORE )  
30.VCC2.5VDUAL&DDR\_VTT  
31.IVDD/VDDQ  
32.Dual/PWR\_Detect  
33.Audio Codec  
34.Audio Interface  
35.LANPHY(RTL8201BL/CL)

	Signature	Date
Designer	Eli Yang	10/04/2005
Layout	Ruru	
Check	Jacy Wu	
Approval	Evan	





# System Block Diagram



PCB size: 244\*204 mm

22U/25DE	5*7 mm
100U/16DE	6.3*11 mm
220U/10DE	6.3*11 mm
470U/16DE	8*11 mm
1000U/10DE	8*14 mm
1200U/16DE	10*25 mm
1800U/63DE	8*20 mm
3300U/25DE	10*25 mm









## VLDT Power Decoupling




Rout with 250 mil trace or a plane


In CPU pins rout >100 mil











D

D

C




C

B






B

A



A



LAYOUT: Place one 1210 10uF capacitor on each end of the VTT island.



LAYOUT: Place alternating caps to GND and VCC2.5V\_DUAL in a single line along VTT island.





 Elitegroup Computer Systems

Title: 761GX-M754

Size: B Document Number: TERMINATION RES Rev: 1.0

Date: Tuesday, October 04, 2005 Sheet: 8 of 35







 **Elitegroup Computer Systems**

**761GX-M754**

Title		Rev
B	761GX-2 MuTIOL and Others	1.0
Date:	Tuesday, October 04, 2005	Sheet 10 of 35


761GX-4

# Ground





**761GX-M754**



Size	Document Number	Rev
B	<b>761GX-3 Power and Ground</b>	1.0
Date:	Tuesday, October 04, 2005	Sheet 11 of 35





761GX-5



LAYOUT: Place HT bypass caps on topside near connected Lokar HT link.



Place these capacitors under NB solder side.





**ECS Elitegroup Computer Systems**

**761GX-M754**


Size	Document Number	Rev
B	761GX-4 Power, Decoupling	1.0

Date: Tuesday, October 04, 2005 Sheet 12 of 35







# Main Clock Generator





Different clock generator with different frequency define table									
CLOCK (ICS953801)	CPUCCLK (MHz)	NBCLK (MHz)	SRC (MHz)	ZCLK (MHz)	PEI-EX (MHz)	PCI (MHz)	(FS4)	(FS3)	(FS2)
100.00	100.00	100.00	100.00	133.33	100.00	33.33	1	0	0
133.33	133.33	100.00	100.00	133.33	100.00	33.33	1	0	0
166.66	166.66	100.00	100.00	133.33	100.00	33.33	1	0	0
200.00	200.00	100.00	100.00	133.33	100.00	33.33	1	0	0
250.00	250.00	100.00	100.00	133.33	100.00	33.33	1	0	1
266.66	266.66	100.00	100.00	133.33	100.00	33.33	1	0	1
333.33	333.33	100.00	100.00	133.33	100.00	33.33	1	0	1
400.00	400.00	100.00	100.00	133.33	100.00	33.33	1	0	1
100.00	125.00	100.00	100.00	133.33	100.00	33.33	1	1	0
133.33	166.66	100.00	100.00	133.33	100.00	33.33	1	1	0
166.66	222.22	100.00	100.00	133.33	100.00	33.33	1	1	0
250.00	333.33	100.00	100.00	133.33	100.00	33.33	1	1	1
266.66	400.00	100.00	100.00	133.33	100.00	33.33	1	1	1
333.33	500.00	100.00	100.00	133.33	100.00	33.33	1	1	1
100.00	125.00	100.00	100.00	133.33	100.00	33.33	1	1	1


SIS 756 CLOCK (IC9593801)						
( )	(FSO)	CPUCLK (MHz)	NBCCLK (MHz)	SRC (MHz)	ZCLK (MHz)	PCI-EX (MHz)
0	133.33	166.66	100.00	133.33	100.00	33.33
1	166.66	222.22	100.00	133.33	100.00	33.33
0	200.00	250.00	100.00	133.33	100.00	33.33
1	250.00	333.33	100.00	133.33	100.00	33.33
0	266.66	400.00	100.00	133.33	100.00	33.33
1	333.33	500.00	100.00	133.33	100.00	33.33
0	134.66	134.66	100.00	134.66	101.00	33.66
1	168.33	168.33	100.00	134.66	101.00	33.66
0	202.00	202.00	100.00	134.66	101.00	33.66
1	252.50	252.50	100.00	134.66	101.00	33.66
0	134.66	168.33	100.00	134.66	101.00	33.66
1	168.33	224.44	100.00	134.66	101.00	33.66
0	200.00	252.00	100.00	134.66	101.00	33.66
1	252.50	306.66	100.00	134.66	101.00	33.66
0	206.00	206.00	100.00	137.33	103.00	34.33
1	206.00	285.70	100.00	137.33	103.00	34.33



































## Temperature Monitor


Choosing method of measuring temperature by either thermistor or diode





FAN pin 3 - SENSE is O' C  
Some Fans are totem pole












CMK-280-S-O



CMK-280-S-O



CMK-280-S-O

