
1.2 Specifications

| | |
|--------------------------|---|
| Platform: | Micro ATX Form Factor: 9.6-in x 7.8-in, 24.4 cm x 19.8 cm |
| CPU: | Supports Socket A (462 pins) for AMD Athlon™ XP / Duron™ processor |
| Chipsets: | North Bridge (K7S41): SiS 741, FSB@400 MHz, AGP 8X/4X North Bridge (K7S41GX): SiS 741GX, FSB@333 MHz, AGP 8X/4X South Bridge: SiS 963L, supports USB 2.0, ATA 133 |
| Memory: | 2 DDR DIMM Slots: DDR1 and DDR2 K7S41: PC3200 (DDR400) / PC2700 (DDR333) / PC2100 (DDR266), Max. 2GB; K7S41GX: PC2700 (DDR333) / PC2100 (DDR266), Max. 2GB |
| IDE: | IDE1: ATA 133 / Ultra DMA Mode 6, IDE2: ATA 133 / Ultra DMA Mode 6, Supports up to 4 IDE devices |
| Floppy Port: | Supports up to 2 floppy disk drives |
| Audio: | 5.1 channels AC'97 Audio |
| LAN: | Speed: 802.3u (10/100 Ethernet), supports Wake-On-LAN |
| Hardware Monitor: | CPU temperature sensing, Chassis temperature sensing, CPU overheat shutdown to protect CPU life (ASRock U-COP)(see CAUTION 1), CPU fan tachometer, Chassis fan tachometer, Voltage monitoring: +12V, +5V, +3V, Vcore |
| PCI slots: | 2 slots with PCI Specification 2.2 |
| AGP slot: | 1 AGP slot, supports 1.5V, 8X/4X AGP card (see CAUTION 2) |
| AMR slot: | 1 slot, supports ASRock MR card (Optional) |
| USB 2.0: | 6 USB 2.0 ports: includes 4 default USB 2.0 ports on the rear panel, plus one connector to support 2 additional USB 2.0 ports (see CAUTION 3) |
| ASRock I/O™: | 1 PS/2 mouse port, 1 PS/2 keyboard port, 1 VGA port, 1 parallel port: ECP/EPP support, 1 RJ 45 port, 4 default USB 2.0 ports, 1 Game port, Audio Jack: Line Out / Line In / Microphone |